EQUIPMENT DESIGN + MANUFACTURE

ZTA.70.Mains Track

STD-000584-0123

Configured Product

Light source	
14mm LES	
ССТ —	
3000К	
CRI -	
SL90	
Beam -	
Wide Flood 51.6°	
Finish —	
Matt Black	
Track adaptor colour	
Black	
Dimming	
DALI	
Attachments	
None	
Secondary Lensing Accessories	
Without accessories	

ZTA.70.Mains Track

EQUIPMENT DESIGN + MANUFACTURE

STD-000584-0123

Environment Downloads Technical Photometry Accessories al

Compliance





ZTA.70. Mains Track

EQUIPMENT DESIGN + MANUFACTURE

STD-000584-0123

Environmental

TM65.2

CIBSE's TM65.2 provides a calculation methodology to assess the embodied carbon in lighting products.

ZTA.70 MAINS TRACK

TM66

CIBSE's TM66 includes a calculator called the Circular Economy Assessment Method (CEAM). An independent metric assessing a luminaire's Circular Economy credentials in terms of product design, materials, manufacturing and ecosystem.

ZTA.70 MAINS TRACK - 2.7

LCA and EPD

A report containing Life Cycle Assessment results, including environmental impacts across the full life cycle of the product. Impacts cover a wide range of effects on the environment, in addition to carbon emissions.

Please contact the Specifier Support team should your project have a requirement for additional environmental reporting. For more information, please click here.

Photometry

These files represent the highest available initial output for each light source in 3000K. Lower outputs and other colour temperatures are available.


Derivatives

We can adapt our fittings to suit your specific needs, here are some examples of what we have done before.

ZTA.70.Mains Track


EQUIPMENT DESIGN + MANUFACTURE

STD-000584-0123



On Board Dimming

Order no. On board dim



ZTA.70.Bay Mains Track

Order no. ZTA.70.Bay Mains Track

Accessories and Attachments

This product can accept up to 2 x lenses and louvres:



Honeycomb louvre for glare control

Order no. ITY-000392



Soft spread lens to product a soft elliptical beam

Order no. ITY-000430




Sharp spread lens to produce a pronounced elliptical beam

Order no. ITY-000431



Diffuser lens used for softening and widening beams

Order no. ITY-



Clear lens can be used as protection from dirt/debris

Order no. ITY-000433



Stipple lens used for softening beams and removing lens artifacts

Order no. ITY-000434

This product can accept one of the following attachments:

ZTA.70.Mains Track

EQUIPMENT DESIGN + MANUFACTURE

STD-000584-0123



Removeable barn doors used to crop beams


Order no. STD-000302



Removeable straight cut or slash cut snoot.

Order no. STD-000612

Related Projects



Young V&A



V&A, Hintze Galleries



National Portrait Gallery

EQUIPMENT DESIGN + MANUFACTURE


STD-000584-0123

Service Commitment





Related Products






ZTA.35.Surface



ZTA.70.Mains Track.Wall Wash



Environmental Technical

Photometry

Accessories

Back to Top