

# STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

## TM65.2 Lighting Calculation

G-CAT

### CIBSE TM65.2 Embodied Carbon Mid-level Calculation

Date:	18/12/2024
Assessor/Organisation:	Stoane Lighting
Contact:	<a href="mailto:sales@mikestoanelighting.com">sales@mikestoanelighting.com</a>

Embodied Carbon Results with 'Mid-Level TM65 Calculation' Method Total

81.40 kg CO<sub>2</sub>e

Through Life (25 year) Embodied Carbon (kgCO<sub>2</sub>e)

First Build  
74.00

Repair  
7.40


1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

25 year product life

### Product Information

Type of Product	Luminaires
Product Weight	2.571 kg
Material Breakdown for at least 95% of the product weight. Breakdown	100.00%
B3: Materials replaced as part of repair	7.401 kgCO <sub>2</sub> e
Energy consumption of the factory per unit of product	44.73 kWh
Location of Manufacture	Edinburgh, Edinburgh, City of, United Kingdom
Product Complexity	Category 2

Materials by % of Product Weight



# STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

## TM65.2 Lighting Calculation: Luminaire

### G-CAT

CIBSE TM65 Embodied Carbon Mid-level Calculation

Embodied Carbon Results Breakdown (kg CO <sub>2</sub> e)	
A1: Material Extraction	19.967
A2: Transport	1.018
A3: Manufacturing	23.857
A4: Transport to Site	0.102
B3: Repair	5.693
C2: Transport	0.034
C3: Waste Processing	11.929
C4: Disposal	0.013

Embodied Carbon Results (kg CO <sub>2</sub> e)	
A1-C4	62.61
A1-C4 with Buffer Factor	81.40

Assumptions	
A1: Material carbon coefficient source	TM65, Table 2.1; TM65.2 Table 9
C4 Percentage of product going to landfill(%)	55% - TM65 Table 4.14

This report was generated using the CIBSE TM65 Manufacturers form 'beta' version V1.3. Released in August 2023  
Stoane Lighting are a UK based company.  
Files are generated for a 'standard' version of the fitting and may not include calculations for accessories or derivatives.  
Only if LED drivers or Power supplies are integral will they be included in the calculation.  
Repair embodied carbon is calculated based on light source and control gear replacement once in the 25 year product life  
Regional variations of the TM65 methodology are being developed; please contact us if there is a requirement for a specific regional assessment where such a local addendum exists.  
For more information please contact us via our website shown below.



This report was produced using the CIBSE documents;  
TM65 Embodied Carbon of MEP Products - June 2021  
TM65.2 Lighting - August 2023

[www.stoanelighting.com](http://www.stoanelighting.com)

