


SL_ZTA.70 Mains Track_9mm
COB_SL98_3000K_1288lm_Wide
Flood_54.1°

Delivered Output: 958 Lumen

Beam details



Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
54.1°	75.1°	86.5°

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
1256 cd	99.3%	97.7%

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1256lx	314lx	140lx	78lx	50lx	35lx	26lx	20lx	16lx	13lx	10lx	9lx	7lx	6lx	6lx	5lx	4lx	4lx	3lx	3lx
116.7fcd	29.2fcd	13fcd	7.3fcd	4.7fcd	3.2fcd	2.4fcd	1.8fcd	1.4fcd	1.2fcd	1fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd

www.stoanelighting.com