STOANE
LIGHTING

# ZTA.70.Pendant

STD-000587-0019

## Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

2700K

Beam

Flood 36.8°

Supply

Constant Current

Finish

Matt Black

Dimming

Driver specific

Cable Length

2000mm

Secondary Lensing Accessories


Without accessories

STOANE LIGHTING

# ZTA.70.Pendant

STD-000587-0019






Modular high-performance, ceiling suspended spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

**Product Description**

ZTA.70.Pendant is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. With height adjustable cables that can be specified to length.

The spotlight can accommodate up to two lens accessories, making it highly customisable for various lighting needs.

**Key Features**

• Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Height adjustable suspension and power cable, can be specified to length.
• High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
• Customisable accessories: can house up to two lens accessories and various attachments.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.





STOANE LIGHTING

# ZTA.70.Pendant

STD-000587-0019

## Compliance

UKCA CE

ETL C US LISTED Intertek

# Technical

| | | | |
|---|---|---|---|
| **Supply** | Remote constant current LED driver required | | |
| **Light source** | 6mm LES COB | 9mm LES COB | 14mm LES COB |
| **Initial output** | **SL90** 8W 32Vf at 250mA<br><br>2700K · 1087lm · 136lm/W<br>3000K · 1133lm · 141lm/W<br>3500K · 1144lm · 143lm/W<br>4000K · 1175lm · 147lm/W<br><br>**SL98** 8.6W 34.4Vf at 250mA<br><br>2400K · 733lm · 85lm/W<br>2700K · 863lm · 100lm/W<br>3000K · 923lm · 107lm/W<br>3500K · 923lm · 107lm/W<br>4000K · 974lm · 113lm/W | **SL90** 11.8W 33.8Vf at 350mA<br><br>2700K · 1822lm · 154lm/W<br>3000K · 1908lm · 161lm/W<br>3500K · 1929lm · 163lm/W<br>4000K · 1919lm · 162lm/W<br><br>**SL98** 10.6W 30.4Vf at 350mA<br><br>2400K · 1085lm · 102lm/W<br>2700K · 1205lm · 113lm/W<br>3000K · 1288lm · 121lm/W<br>3500K · 1313lm · 124lm/W<br>4000K · 1352lm · 127lm/W | **SL90** 20.9W 34.8Vf at 600mA<br><br>2700K · 3097lm · 148lm/W<br>3000K · 3243lm · 155lm/W<br>3500K · 3280lm · 157lm/W<br>4000K · 3261lm · 156lm/W<br><br>**SL98** 23.5W 33.5Vf at 700mA<br><br>2400K · 2362lm · 101lm/W<br>2700K · 2669lm · 114lm/W<br>3000K · 2852lm · 122lm/W<br>3500K · 2909lm · 124lm/W<br>4000K · 2973lm · 127lm/W |
| **Light distribution** | Very Narrow 7.3°<br>Very Narrow 29.6°<br>Narrow 11°<br>Medium 26.7°<br>Flood 36.8°<br>Wide Flood 55.4°<br>Extra Wide Flood 85.4° | Very Narrow 11.1°<br>Narrow 14.4°<br>Narrow 2 15.1°<br>Medium 25.1°<br>Flood 35.1°<br>Wide Flood 54.1°<br>Extra Wide Flood 82.9° | Narrow 16.9°<br>Narrow 2 21.4°<br>Medium 22°<br>Medium 2 24.7°<br>Flood 32.4°<br>Wide Flood 51.6°<br>Extra Wide Flood 79.6° |

STOANE LIGHTING

# ZTA.70.Pendant

STD-000587-0019

| | |
|---|---|
| **Lumen maintenance** | L90 B0 in excess of 94,000 hours |
| **Colour consistency** | 2 SDCM |
| **IP rating** | IP20 |
| **Weight** | 0.75kg |

## Service Commitment

ReNew

5 Year Warranty
25 Year Duty of Care