

ZTA.35.Surface

STD-000558-0091

Configured Product

Light Source

SL90

Light Source Size

4mm LES

CCT

2700K

Beam

Narrow 13.6°

Finish

Matt Black

Cable route

Through Base

Secondary Lensing Accessories

Without accessories

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.35.Surface

STD-000558-0091

Compliance



Technical

Supply	Remote constant current LED driver required	
Light source	4mm LES COB	6mm LES COB
Initial output	SL90 8.8W 35.1Vf at 250mA	SL90 8W 32Vf at 250mA
	2700K · 972lm · 111lm/W	2700K · 1087lm · 136lm/W
	3000K · 1013lm · 115lm/W	3000K · 1133lm · 141lm/W
	3500K · 1023lm · 116lm/W	3500K · 1144lm · 143lm/W
	4000K · 1051lm · 120lm/W	4000K · 1175lm · 147lm/W
	SL98 4.3W 17.2Vf at 250mA	SL98 8.6W 34.4Vf at 250mA
	2400K · 355lm · 83lm/W	2400K · 733lm · 85lm/W
	2700K · 418lm · 97lm/W	2700K · 863lm · 100lm/W
	3000K · 446lm · 104lm/W	3000K · 923lm · 107lm/W
	3500K · 446lm · 104lm/W	3500K · 923lm · 107lm/W
	4000K · 471lm · 110lm/W	4000K · 974lm · 113lm/W
Light distribution	Narrow 13.6°	Narrow 17.8°
	Medium 22°	Medium 23°
	Flood 35.4°	Flood 34.6°
	Wide Flood 52.8°	Wide Flood 54.5°
	Zoom 17.2° - 46.8°	Zoom 21.6° - 44.9°
Lumen maintenance	L90 B0 in excess of 94,000 hours	
Colour consistency	2 SDCM	
IP rating	IP20	
Weight	0.31kg	

Service Commitment

