

ZTA.50.Bay

STD-000564-0035

Configured Product

Light Source _____

SL90

Light Source Size _____

6mm LES

CCT _____

2700K

Beam _____

Very Narrow 13.9°

Finish _____

Matt Black

Dimming _____


Driver specific

Cable Length _____

500mm

Secondary Lensing Accessories _____

Without accessories



Modular high-performance, ceiling mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description

ZTA.50.Bay is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.

Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: can house up to two lens accessories and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.50.Bay

STD-000564-0035

Compliance

**UK
CA** 



Technical

Supply Remote constant current LED driver required

Light source	6mm LES COB	9mm LES COB
---------------------	-------------	-------------

Initial output	SL90 8W 32Vf at 250mA	SL90 11.8W 33.8Vf at 350mA
-----------------------	------------------------------	-----------------------------------

2700K	• 1087lm • 136lm/W	2700K	• 1822lm • 154lm/W
3000K	• 1133lm • 141lm/W	3000K	• 1908lm • 161lm/W
3500K	• 1144lm • 143lm/W	3500K	• 1929lm • 163lm/W
4000K	• 1175lm • 147lm/W	4000K	• 1919lm • 162lm/W

SL98 8.6W 34.4Vf at 250mA	SL98 10.6W 30.4Vf at 350mA		
2700K	• 863lm • 100lm/W	2700K	• 1205lm • 113lm/W
3000K	• 923lm • 107lm/W	3000K	• 1288lm • 121lm/W
3500K	• 923lm • 107lm/W	3500K	• 1313lm • 124lm/W
4000K	• 974lm • 113lm/W	4000K	• 1352lm • 127lm/W

Light distribution	Very Narrow 13.9°	Narrow 17.4°
	Narrow 14.7°	Narrow 2 18.8°
	Medium 24.1°	Medium 25.3°
	Flood 36.7°	Flood 34.1°
	Wide Flood 51.7°	Wide Flood 46.6°

Lumen maintenance	L90 B0 in excess of 94,000 hours
--------------------------	----------------------------------

Colour consistency	2 SDCM
---------------------------	--------

Colour maintenance	± 0.007 Δu'v'
---------------------------	---------------

IP rating	IP20
------------------	------

Weight	0.31kg
---------------	--------

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.50.Bay

STD-000564-0035

Service Commitment

