

## Toad

STD-000552-0034

### Configured Product

Light Source

SL90

Light Source Size

9mm LES

CCT

2700K

Beam

Very Narrow 11.6°

Finish

Matt Black

Attachments

None

Secondary Lensing Accessories

Without accessories



**STOANE LIGHTING**

EQUIPMENT DESIGN + MANUFACTURE

Toad

STD-000552-0034

Compliance



# Technical

<b>Supply</b>	Remote constant current LED driver required	
<b>Light source</b>	9mm LES COB	14mm LES COB
<b>Initial output</b>	<p><b>SL90</b> 25.4W 36.3Vf at 700mA</p> <p>2700K · 3388lm · 133lm/W            3000K · 3548lm · 140lm/W            3500K · 3587lm · 141lm/W            4000K · 3569lm · 140lm/W</p> <p><b>SL98</b> 30.4W 33.8Vf at 900mA</p> <p>2700K · 2740lm · 90lm/W            3000K · 2928lm · 96lm/W            3500K · 3008lm · 99lm/W            4000K · 3074lm · 101lm/W</p>	<p><b>SL90</b> 30.7W 36.1Vf at 850mA</p> <p>2700K · 4232lm · 100lm/W            3000K · 4431lm · 107lm/W            3500K · 4482lm · 107lm/W            4000K · 4455lm · 113lm/W</p> <p><b>SL98</b> 30.8W 34.2Vf at 900mA</p> <p>2700K · 3370lm · 109lm/W            3000K · 3600lm · 117lm/W            3500K · 3699lm · 120lm/W            4000K · 3667lm · 115lm/W</p>
<b>Light distribution</b>	<p>Very Narrow 11.6°            Medium 34.7°            Flood 42.8°            Wide Flood 45.3°</p>	<p>Narrow 13.8°            Medium 38.9°            Flood 45.1°            Wide Flood 52.6°</p>
<b>Lumen maintenance</b>	L90 B0 in excess of 94,000 hours	
<b>Colour consistency</b>	2 SDCM	
<b>IP rating</b>	IP66	
<b>Weight</b>	2.37kg	

Service Commitment

