

# ZTA.50.Mains Track.Zoom

STD-000572-0045

## Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

2700K

Beam

Zoom 13.7° to 48.1°

Finish

Matt Black

Track adaptor colour

White

Dimming


Local Dim

Attachments

None

Secondary Lensing Accessories

Without accessories



Modular high-performance, mains track-mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

## Product Description

ZTA.50.Mains Track.Zoom is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between fixed optic, Wall Wash and Framing projector options.

## Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Zoom optics can be easily swapped to Fixed, Wall Wash and additional framer attachments.
- Versatile Adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- Broad compatibility: 3-circuit adapter supports multiple track systems (Stucchi, Eutrac, Global Pulse).
- Advanced dimming options: On-board, DALI, 0-10V, and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: can house up to one lens accessory and various attachments.
- Ceiling mounting only: designed exclusively for ceiling installations.

## Compliance



# Technical

|                    |                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply             | 230V/240V via 3 circuit track                                                                                                                                                                                                                                                                                                                                                                       |
| Light source       | 6mm LES COB                                                                                                                                                                                                                                                                                                                                                                                         |
| Initial output     | <div>SL90 8W 32Vf at 250mA</div> <div>2700K · 1087lm · 136lm/W</div> <div>3000K · 1133lm · 141lm/W</div> <div>3500K · 1144lm · 143lm/W</div> <div>4000K · 1175lm · 147lm/W</div> <div>SL98 8.6W 34.4Vf at 250mA</div> <div>2400K · 733lm · 85lm/W</div> <div>2700K · 863lm · 100lm/W</div> <div>3000K · 923lm · 107lm/W</div> <div>3500K · 923lm · 107lm/W</div> <div>4000K · 974lm · 113lm/W</div> |
| Light distribution | Zoom 13.7° – 48.1°                                                                                                                                                                                                                                                                                                                                                                                  |
| Lumen maintenance  | L90 B0 in excess of 94,000 hours                                                                                                                                                                                                                                                                                                                                                                    |
| Colour consistency | 2 SDCM                                                                                                                                                                                                                                                                                                                                                                                              |
| IP rating          | IP20                                                                                                                                                                                                                                                                                                                                                                                                |
| Weight             | 0.56kg                                                                                                                                                                                                                                                                                                                                                                                              |

---

Service Commitment

