STOANE
LIGHTING

# Mole

STD-000031-0073

## Configured Product

CCT

2200K

Beam

Wide Flood 60.6°

Finish


Anodised Clear


STOANE LIGHTING

# Mole

STD-000031-0073






Miniature exterior in-ground recessed fixed uplighter, for enhancing architectural details, gardens and pathways.

**Product Description**

The Mole is an IP66 rated fixed exterior up light, designed to highlight textures, add depth to trees, sculptures, facades and other outdoor features as well as for use indoors. Perfect for both commercial and residential applications, ideal for bringing spaces to life after dark.

Machined from recycled aluminium with an anodised finish for enhanced durability and a toughened glass lens.

**Key Features**

• Sustainable construction: made from recycled aluminium with a long-lasting anodised finish. Specialist finishes available on request.

• Interchangeable optics to allow Very Narrow to Wide Flood with the addition of secondary lenses to create elliptical beam options.

• Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.

• High-performance lighting: up to 97 CRI LEDs.

• First fix Installation sleeve available for mounting.



STOANE
LIGHTING

# Mole

STD-000031-0073

## Compliance

STOANE LIGHTING

# Mole

STD-000031-0073

## Technical

| | |
|---|---|
| **Supply** | Remote constant current LED driver required |
| **Light source** | SL Star |
| **Initial output** | 2W 2.9Vf at 700mA<br>**80 CRI**<br>2200K • 150lm • 71lm/W<br>**90 CRI**<br>2400K • 210lm • 105lm/W<br>**95 CRI**<br>2700K • 167lm • 82lm/W<br>3000K • 177lm • 87lm/W<br>3500K • 187lm • 92lm/W<br>4000K • 197lm • 97lm/W |
| **Light distribution** | Very Narrow 8.9°<br>Narrow 11.5°<br>Medium 16.4°<br>Flood 37.7°<br>Wide Flood 60.6°<br>Elliptical 16.1° x 47.3° |
| **Lumen maintenance** | L70 B50 >66,000 hours |
| **Colour consistency** | 2 SDCM |
| **Colour maintenance** | ± 0.007 Δu'v' |
| **IP rating** | IP66 |
| **Weight** | 0.03kg |

STOANE
LIGHTING

# Mole

STD-000031-0073

---

## Service Commitment

