

## Exterior LED Channel

STD-000023-0067

### Configured Product

LED \_\_\_\_\_

SL G3.2 Strip Standard Output

CCT \_\_\_\_\_

3000K

Length \_\_\_\_\_

500mm

Finish \_\_\_\_\_


Anodised Black

Mounting Method \_\_\_\_\_

Hinge

Diffuser \_\_\_\_\_

Frosted




Linear lighting system, typically for under seat, planter and handrail lighting applications.

**Product Description**

The Exterior LED Channel is a compact IP66 recycled aluminium extrusion, engineered to provide both subtle accent lighting or deliver brighter illumination within exterior seating, planter or handrail lighting applications. The innovative extrusion design allows for ease of installation and the product can be offered with either a frosted diffuser with a soft glow effect, or a clear cover for higher output applications. Custom glare baffles and clamping system options available on request. Fully encapsulated the product is designed with an innovative anti wick system to avoid water ingress.

**Key Features**

- Sustainable construction: made from recycled aluminium.
- Innovative mounting system allowing for ease of installation and maintenance.
- High and low output options available with a custom frosted diffuser for a soft lit effect or clear cover for higher output applications.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 90 CRI LEDs.
- Not suitable for in-ground applications.



## Compliance



---

## Service Commitment



---

## Technical

Light Source

Standard Output LED Strip

90 CRI

1496lm/m initial output at 3000K  
89lm/W

High Output LED Strip

90 CRI

2702lm/m initial output at 3000K  
86.6lm/W

Light

Distribution

Clear cover 103.4° x 115.1°

Diffuser 112.4° x 110.6°