STOANE
LIGHTING

# Exterior LED Channel

STD-000023-0085

## Configured Product

LED

SL G3.2 Strip High Output

CCT

2700K

Length

TBC

Finish

Custom Painted

Mounting Method

Hinge

Diffuser


Frosted

STOANE
LIGHTING

# Exterior LED Channel

STD-000023-0085







Linear lighting system, typically for under seat, planter and handrail lighting applications.

**Product Description**

The Exterior LED Channel is a compact IP66 recycled aluminium extrusion, engineered to provide both subtle accent lighting or deliver brighter illumination within exterior seating, planter or handrail lighting applications.
The innovative extrusion design allows for ease of installation and the product can be offered with either a frosted diffuser with a soft glow effect, or a clear cover for higher output applications.
Custom glare baffles and clamping system options available on request.
Fully encapsulated the product is designed with an innovative anti wick system to avoid water ingress.

**Key Features**

• Sustainable construction: made from recycled aluminium.
• Innovative mounting system allowing for ease of installation and maintenance.
• High and low output options available with a custom frosted diffuser for a soft lit effect or clear cover for higher output applications.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 90 CRI LEDs.
• Not suitable for in-ground applications.



STOANE LIGHTING

# Exterior LED Channel

STD-000023-0085

## Compliance

UK CA CE

---

## Service Commitment

ReNew

5 Year Warranty
25 Year Duty of Care

---

## Technical

| | | |
|---|---|---|
| **Light Source** | **Standard Output LED Strip**<br>**90 CRI**<br>1496lm/m initial output at 3000K<br>89lm/W | **High Output LED Strip**<br>**90 CRI**<br>2702lm/m initial output at 3000K<br>86.6lm/W |
| **Light Distribution** | Clear cover 103.4° x 115.1°<br>Diffuser 112.4° x 110.6° | |