

Mole

STD-000031-0054

Configured Product

CCT _____


3000K

Beam _____

TBC

Finish _____

Anodised Black



Miniature exterior in-ground recessed fixed uplighter, for enhancing architectural details, gardens and pathways.

Product Description

The Mole is an IP66 rated fixed exterior up light, designed to highlight textures, add depth to trees, sculptures, facades and other outdoor features as well as for use indoors. Perfect for both commercial and residential applications, ideal for bringing spaces to life after dark.

Machined from recycled aluminium with an anodised finish for enhanced durability and a toughened glass lens.

Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised finish. Specialist finishes available on request.
- Interchangeable optics to allow Very Narrow to Wide Flood with the addition of secondary lenses to create elliptical beam options.
- Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 97 CRI LEDs.
- First fix Installation sleeve available for mounting.



Compliance



Technical

Supply Remote constant current LED driver required

Light source SL Star

Initial output 95CRI 2W 2.8Vf at 700mA

2700K • 179lm • 90lm/W

3000K • 192lm • 96lm/W

3500K • 204lm • 102lm/W

4000K • 219lm • 110lm/W

Light distribution Very Narrow 8.5°

Narrow 12.4°

Medium 21.3°

Flood 41.3°

Wide Flood 53.7°

Elliptical 12.6° x 46.9°

Lumen maintenance L70 B50 >66,000 hours

Colour consistency 2 SDCM

Colour maintenance $\pm 0.007 \Delta u'v'$

IP rating IP66

Weight 0.03kg

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Mole

STD-000031-0054

Service Commitment

