STOANE
LIGHTING

Mole

STD-000031-0070

Configured Product

CCT

2700K

Beam

Medium 16.4°

Finish

TBC

STOANE LIGHTING

Mole

STD-000031-0070





Miniature exterior in-ground recessed fixed uplighter, for enhancing architectural details, gardens and pathways.

Product Description

The Mole is an IP66 rated fixed exterior up light, designed to highlight textures, add depth to trees, sculptures, facades and other outdoor features as well as for use indoors. Perfect for both commercial and residential applications, ideal for bringing spaces to life after dark.

Machined from recycled aluminium with an anodised finish for enhanced durability and a toughened glass lens.

Key Features

• Sustainable construction: made from recycled aluminium with a long-lasting anodised finish. Specialist finishes available on request.

• Interchangeable optics to allow Very Narrow to Wide Flood with the addition of secondary lenses to create elliptical beam options.

• Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.

• High-performance lighting: up to 97 CRI LEDs.

• First fix Installation sleeve available for mounting.

STOANE
LIGHTING

Mole

STD-000031-0070

Compliance

STOANE
LIGHTING

Mole

STD-000031-0070

Technical

Supply	Remote constant current LED driver required
Light source	SL Star
Initial output	2W 2.9Vf at 700mA **80 CRI** 2200K • 150lm • 71lm/W **90 CRI** 2400K • 210lm • 105lm/W **95 CRI** 2700K • 167lm • 82lm/W 3000K • 177lm • 87lm/W 3500K • 187lm • 92lm/W 4000K • 197lm • 97lm/W
Light distribution	Very Narrow 8.9° Narrow 11.5° Medium 16.4° Flood 37.7° Wide Flood 60.6° Elliptical 16.1° x 47.3°
Lumen maintenance	L70 B50 >66,000 hours
Colour consistency	2 SDCM
Colour maintenance	± 0.007 Δu'v'
IP rating	IP66
Weight	0.03kg

STOANE
LIGHTING

Mole

STD-000031-0070

Service Commitment