STOANE
LIGHTING

Firefly

STD-000036-0012

Configured Product

CCT

2700K

Length

TBC

Finish

Anodised Black

Diffuser

TBC

Cable Length


500mm

STOANE
LIGHTING

Firefly

STD-000036-0012





Exterior landscape reed light, designed for soft and hard landscaping applications, for enhancing green spaces and pathways. Its slim carbon fibre stem yields in wind to give a gentle sway.

Product Description
The Firefly is a small form factor IP66 rated exterior reed light, designed to provide a soft, low level 360° lighting distribution via a customised impact resistant frosted diffuser system.
Also available with a clear flame polished diffuser to concentrate light at the tip if a "twinkle" effect is desired.
Used to enhance walkways and greenery without overwhelming the natural surroundings.
Carbon fibre stem to allow movement in the wind, lengths can be individually specified to order.

Key Features
• Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Ability to specify individual stem lengths and bespoke mount plate options to create product clusters.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 97 CRI LEDs.
• Special SPD LEDs such as Red Orange are available on request.
• Ground spike and fixed mount plate options available for soft and hard landscaping applications.





STOANE
LIGHTING

Firefly

STD-000036-0012

Compliance

UK CA CE

c ETL LISTED us
Intertek

STOANE
LIGHTING

Firefly

STD-000036-0012

Technical

Supply	Remote constant current LED driver required
Light source	SL Type S
Initial output	1.4W 2.8Vf at 500mA **80 CRI** 2200K • 116lm • 77lm/W **90 CRI** 2400K • 157lm • 115lm/W **95 CRI** 2700K • 125lm • 88lm/W 3000K • 133lm • 94lm/W 3500K • 140lm • 99lm/W 4000K • 148lm • 104lm/W
Light distribution	Clear 54.8° Diffused 109.2°
Lumen maintenance	L70 B50 >66,000 hours
Colour consistency	2 SDCM
Colour maintenance	± 0.007 Δu'v'
IP rating	IP66
Weight	0.2kg

STOANE
LIGHTING

Firefly

STD-000036-0012

Service Commitment



