

## Firefly

STD-000036-0034

### Configured Product

CCT \_\_\_\_\_

2700K

Length \_\_\_\_\_

Length:

Finish \_\_\_\_\_


Anodised Black

Diffuser \_\_\_\_\_

TBC

Cable Length \_\_\_\_\_

500mm



Exterior landscape reed light, designed for soft and hard landscaping applications, for enhancing green spaces and pathways. Its slim carbon fibre stem yields in wind to give a gentle sway.

#### Product Description

The Firefly is a small form factor IP66 rated exterior reed light, designed to provide a soft, low level 360° lighting distribution via a customised impact resistant frosted diffuser system.

Also available with a clear flame polished diffuser to concentrate light at the tip if a "twinkle" effect is desired.

Used to enhance walkways and greenery without overwhelming the natural surroundings.

Carbon fibre stem to allow movement in the wind, lengths can be individually specified to order.

#### Key Features

- Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Ability to specify individual stem lengths and bespoke mount plate options to create product clusters.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 97 CRI LEDs.
- Special SPD LEDs such as Red Orange are available on request.
- Ground spike and fixed mount plate options available for soft and hard landscaping applications.



## Compliance



## Technical

**Supply** Remote constant current LED driver required

**Light source** SL Type S

**Initial output** 95 CRI 1.4W 2.75Vf at  
500mA

2700K • 139lm • 99lm/W  
3000K • 148lm • 105lm/W  
3500K • 158lm • 112lm/W  
4000K • 169lm • 120lm/W

**Light distribution** Clear 54.8°  
Diffused 109.2°

**Lumen maintenance** L70 B50 >66,000 hours

**Colour consistency** 2 SDCM

**Colour maintenance**  $\pm 0.007 \Delta u'v'$

**IP rating** IP66

**Weight** 0.2kg

**STOANE LIGHTING**

EQUIPMENT DESIGN + MANUFACTURE

**Firefly**

STD-000036-0034

---

## Service Commitment

