

Firefly

STD-000036-0055

Configured Product

CCT _____

4000K

Length _____

1000mm

Finish _____


Anodised Clear

Diffuser _____

Clear

Cable Length _____

500mm



Exterior landscape reed light, designed for soft and hard landscaping applications, for enhancing green spaces and pathways. Its slim carbon fibre stem yields in wind to give a gentle sway.

Product Description

The Firefly is a small form factor IP66 rated exterior reed light, designed to provide a soft, low level 360° lighting distribution via a customised impact resistant frosted diffuser system.


Also available with a clear flame polished diffuser to concentrate light at the tip if a "twinkle" effect is desired.

Used to enhance walkways and greenery without overwhelming the natural surroundings.

Carbon fibre stem to allow movement in the wind, lengths can be individually specified to order.

Key Features

- Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Ability to specify individual stem lengths and bespoke mount plate options to create product clusters.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 97 CRI LEDs.
- Special SPD LEDs such as Red Orange are available on request.
- Ground spike and fixed mount plate options available for soft and hard landscaping applications.



Compliance



Technical

Supply	Remote constant current LED driver required
Light source	SL Type S
Initial output	95 CRI 1.4W 2.75Vf at 500mA 2700K · 139lm · 99lm/W 3000K · 148lm · 105lm/W 3500K · 158lm · 112lm/W 4000K · 169lm · 120lm/W
Light distribution	Clear 54.8° Diffused 109.2°
Lumen maintenance	L70 B50 >66,000 hours
Colour consistency	2 SDCM
Colour maintenance	± 0.007 Δu'v'
IP rating	IP66
Weight	0.2kg

Service Commitment

