

## Firefly

STD-000036-0076

### Configured Product

CCT \_\_\_\_\_

2700K

Length \_\_\_\_\_

500mm

Finish \_\_\_\_\_

Custom Painted

Diffuser \_\_\_\_\_

Frosted

Cable Length \_\_\_\_\_

500mm



Exterior landscape reed light, designed for soft and hard landscaping applications, for enhancing green spaces and pathways. Its slim carbon fibre stem yields in wind to give a gentle sway.

## Product Description

The Firefly is a small form factor IP66 rated exterior reed light, designed to provide a soft, low level 360° lighting distribution via a customised impact resistant frosted diffuser system.


Also available with a clear flame polished diffuser to concentrate light at the tip if a "twinkle" effect is desired.

Used to enhance walkways and greenery without overwhelming the natural surroundings.

Carbon fibre stem to allow movement in the wind, lengths can be individually specified to order.

## Key Features

- Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Ability to specify individual stem lengths and bespoke mount plate options to create product clusters.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 97 CRI LEDs.
- Special SPD LEDs such as Red Orange are available on request.
- Ground spike and fixed mount plate options available for soft and hard landscaping applications.



## Compliance



## Technical

Supply	Remote constant current LED driver required
Light source	SL Type S
Initial output	95 CRI 1.4W 2.75Vf at 500mA  2700K · 139lm · 99lm/W 3000K · 148lm · 105lm/W 3500K · 158lm · 112lm/W 4000K · 169lm · 120lm/W
Light distribution	Clear 54.8° Diffused 109.2°
Lumen maintenance	L70 B50 >66,000 hours
Colour consistency	2 SDCM
Colour maintenance	± 0.007 Δu'v'
IP rating	IP66
Weight	0.2kg

## Service Commitment

