STOANE
LIGHTING

# Firefly

STD-000036-0080

## Configured Product

CCT

2700K

Length

1000mm

Finish

Anodised Black

Diffuser

Clear

Cable Length


500mm

STOANE
LIGHTING

# Firefly

STD-000036-0080






Exterior landscape reed light, designed for soft and hard landscaping applications, for enhancing green spaces and pathways. Its slim carbon fibre stem yields in wind to give a gentle sway.

**Product Description**
The Firefly is a small form factor IP66 rated exterior reed light, designed to provide a soft, low level 360° lighting distribution via a customised impact resistant frosted diffuser system.
Also available with a clear flame polished diffuser to concentrate light at the tip if a "twinkle" effect is desired.
Used to enhance walkways and greenery without overwhelming the natural surroundings.
Carbon fibre stem to allow movement in the wind, lengths can be individually specified to order.

**Key Features**
• Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Ability to specify individual stem lengths and bespoke mount plate options to create product clusters.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 97 CRI LEDs.
• Special SPD LEDs such as Red Orange are available on request.
• Ground spike and fixed mount plate options available for soft and hard landscaping applications.





STOANE
LIGHTING

# Firefly

STD-000036-0080

## Compliance

STOANE LIGHTING

# Firefly

STD-000036-0080

## Technical

| | |
|---|---|
| **Supply** | Remote constant current LED driver required |
| **Light source** | SL Type S |
| **Initial output** | 1.4W 2.8Vf at 500mA<br><br>**80 CRI**<br>2200K • 116lm • 77lm/W<br>**90 CRI**<br>2400K • 157lm • 115lm/W<br>**95 CRI**<br>2700K • 125lm • 88lm/W<br>3000K • 133lm • 94lm/W<br>3500K • 140lm • 99lm/W<br>4000K • 148lm • 104lm/W |
| **Light distribution** | Clear 54.8°<br>Diffused 109.2° |
| **Lumen maintenance** | L70 B50 >66,000 hours |
| **Colour consistency** | 2 SDCM |
| **Colour maintenance** | ± 0.007 Δu'v' |
| **IP rating** | IP66 |
| **Weight** | 0.2kg |

STOANE
LIGHTING

# Firefly

STD-000036-0080

---

## Service Commitment

