STOANE
LIGHTING

Tadpole Spike

STD-000067-0051

Configured Product

CCT

2700K

Beam

TBC

Finish

Custom Painted

Attachments

Straight/Slash reversible snoot (specified separately)

Cable Length


500mm

STOANE
LIGHTING

Tadpole Spike

STD-000067-0051





High-performance exterior spotlight system, for soft landscaping to illuminate exterior architectural details and landscape illumination.

Product Description
The Tadpole Spike is an IP66 exterior rated, adjustable and lockable spotlight.
Constructed from precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.
Additional mounting options for spike and surface mount applications.

Key Features
• Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Fixed optics can be easily swapped from Very Narrow to Flood to elliptical beam options
• Snoot and Cowl options available.
• Surface and Wall mounted options available.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 97 CRI LEDs with interchangeable optical systems.

STOANE
LIGHTING

Tadpole Spike

STD-000067-0051



Compliance

STOANE LIGHTING

Tadpole Spike

STD-000067-0051

Technical

Supply	Remote constant current LED driver required
Light source	SL Star
Initial output	**95CRI** 2W 2.9Vf at 700mA 2700K • 167lm • 82lm/W 3000K • 177lm • 87lm/W 3500K • 187lm • 92lm/W 4000K • 197lm • 97lm/W
Light distribution	Very Narrow 8.9° Narrow 11.5° Medium 16.4° Flood 37.7° Wide Flood 60.6° Elliptical 12.9° x 47.8°
Lumen maintenance	L70 B50 >66,000 hours
Colour consistency	2 SDCM
Colour maintenance	± 0.007 Δu'v'
IP rating	IP66
Weight	0.19kg

STOANE
LIGHTING

Tadpole Spike

STD-000067-0051

Service Commitment



