

## ZTA.50.Surface STD-000179-0263

Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

### Product Description

ZTA.50.Surface is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between fixed optic, [Wall Wash](#), [Zoom](#) and [Framing projector](#) options.

### Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Fixed optics can be easily swapped to Zoom, Wall Wash and additional framer attachments.
- Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: can house up to one lens accessory and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



# STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

## ZTA.50.Surface STD-000179-0263

### Configured Product

Light source

6mm LES

CCT

Tuneable White source available. Please contact us for more information.

3000K

CRI

90

Beam

Medium 24.1°

Supply

Constant Current

Finish

Please contact us for custom finishing requirements

RAL 9010 Pure White

Dimming

N/A

Attachments

None

Cable route

"Flying Lead" is cable exit through rear of lamp tube.

Flying Lead

Cable Length

500mm

# STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

## ZTA.50.Surface STD-000179-0263

Secondary Lensing Accessories

With accessories