

Toad (ATEX)

STD-000273-0050

Configured Product

Light Source

SL90

Light Source Size

14mm LES

CCT

2400K

Beam

Flood 45.1°

Finish

Standard Painted

Attachments

None

Secondary Lensing Accessories

Without accessories



Special ATEX rated high-performance exterior spotlight, for ceiling and wall mounting to illuminate exterior architectural details.

Product Description

This product is an ATEX rated version of the Toad Type X luminaire, suitable for use in explosive atmospheres. A high power IP66 exterior rated, adjustable and lockable spotlight.

Constructed from precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.

Provided with interchangeable optics from Very Narrow to Wide Flood, a honeycomb louvre can be added for glare control. Snoot option is also available.

Key Features

- Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish.
- Fixed optics can be easily swapped from Very Narrow to Flood options, capable of holding up to two additional lens accessories.
- Snoot option available.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



Compliance



Service Commitment



Techn
ical

Light Source

19mm LES COB
80 CRI 1050mA
3850lm initial output at 3000K
126lm/W

Light

Distribution

Narrow 13.2°
Medium 22.3°
Flood 40.4°
Wide Flood 56.2°