STOANE
LIGHTING

Toad (ATEX)

STD-000273-0051

Configured Product

Light Source

SL90

Light Source Size

9mm LES

CCT

2700K

Beam

Wide Flood 45.3°

Finish

Anodised Black

Attachments

Straight/Slash Cut Snoot (specified separately)

Secondary Lensing Accessories

Honeycomb louvre

STOANE LIGHTING

Toad (ATEX)

STD-000273-0051

Special ATEX rated high-performance exterior spotlight, for ceiling and wall mounting to illuminate exterior architectural details.

Product Description

This product is an ATEX rated version of the Toad Type X luminaire, suitable for use in explosive atmospheres. A high power IP66 exterior rated, adjustable and lockable spotlight.
Constructed from precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.
Provided with interchangeable optics from Very Narrow to Wide Flood, a honeycomb louvre can be added for glare control. Snoot option is also available.

Key Features

• Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish.
• Fixed optics can be easily swapped from Very Narrow to Flood options, capable of holding up to two additional lens accessories.
• Snoot option available.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.

STOANE LIGHTING

Toad (ATEX)

STD-000273-0051

Compliance

UKCA CE

Service Commitment

ReNew

5 Year Warranty
25 Year Duty of Care

STOANE
LIGHTING

Toad (ATEX)

STD-000273-0051

Technical

	19mm LES COB
Light Source	80 CRI 1050mA 3850lm initial output at 3000K 126lm/W
Light Distribution	Narrow 13.2° Medium 22.3° Flood 40.4° Wide Flood 56.2°