STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Amanita

STD-000409-0049

Configured Product

CCT

3000K

Finish

Custom Painted

Mounting Method

Mount Disc (buried)

Cable Length

500mm

Stem Height

Custom

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Amanita

STD-000409-0049



Exterior landscape accent lighting system, designed for both soft and hard landscaping applications, it can be used both in ground and on tabletops.

Product Description

The Amanita is a small form factor IP66 rated exterior accent light, designed to provide a soft, low level, 360° lighting distribution via a customised impact resistant frosted diffuser.
When orientated directly downwards the product provides a **BUG rating** of B0 U0 G0.
Providing up to 20.6° of lockable tilt adjustment and both spike and fixed mount plates available.

Key Features

- Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Versatile adjustment providing up to 20.6° of tilt with locking mechanism.
- Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.
- High-performance lighting: Up to 97 CRI LEDs.
- Special SPD LEDs available on request.
- Ground spike and fixed mount plate options available for soft and hard landscaping applications.

Compliance

UK CA CE

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Amanita

STD-000409-0049

Technical

Supply	Remote constant current LED driver required
Light source	SL Star
Initial output	**95 CRI** 6W 8.4Vf at 700mA 2700K • 537lm • 90lm/W 3000K • 576lm • 96lm/W 3500K • 612lm • 102lm/W 4000K • 657lm • 110lm/W
Light distribution	Downward 96.2°
Lumen maintenance	L70 B50 >66,000 hours
Colour consistency	2 SDCM
Colour maintenance	± 0.007 Δu'v'
IP rating	IP66
Weight	0.65kg

Service Commitment

ReNew

5 Year Warranty
25 Year Duty of Care