STOANE
LIGHTING

# Mini G-Cat

STD-000410-0124

## Configured Product

CCT

2400K

Beam

Low Glare Diffuser

Supply

Two Circuits

Finish

Matt Black

STOANE LIGHTING

# Mini G-Cat

STD-000410-0124





Compact exterior lighting system, to enhance outdoor public spaces, pathways and more intimate hospitality and high end residential applications.

**Product Description**
The Mini G-Cat is an award winning IP66 exterior rated compact lighting system that offers versatile lighting options.

Clear polished, internally frosted Decorative Globe is joined by:
**Low Glare** A custom acrylic designed to minimise upward light spill. Suitable for Dark Sky applications.
**Technical Optics** Very Narrow - Wide Flood options supplied with low glare snoot and frosted glass with provision for one lens accessory.

**Key Features**
• Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• IK10 rated.
• Adjustable beam angles with interchangeable optics with no upward light spill.
• Specialist Globe diffuser for decorative glow.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
• High-performance lighting: Up to 90 CRI LEDs




STOANE LIGHTING

# Mini G-Cat

STD-000410-0124

## Compliance

## Technical

| | |
|---|---|
| **Supply** | Remote constant current LED driver required |
| **Light source** | 6mm LES COB |
| **Initial output** | **90 CRI** 6.3W 9Vf at 700mA<br>2400K · 706lm · 119lm/W<br>2700K · 763lm · 129lm/W<br>3000K · 792lm · 134lm/W<br>3500K · 809lm · 137lm/W<br>4000K · 826lm · 140lm/W |
| **Light distribution** | Decorative Globe 84.4°<br>Low Glare 63.7°<br>Very Narrow 12.6°<br>Medium 25.5°<br>Flood 36.6°<br>Wide Flood 51.3° |
| **Colour consistency** | 3 SDCM |
| **IP rating** | IP66 |
| **IK rating** | IK10 |
| **Weight** | 0.87kg |

STOANE
LIGHTING

# Mini G-Cat

STD-000410-0124

---

## Service Commitment




