

# Mini G-Cat

STD-000410-0144

## Configured Product

CCT 

---

2400K

Beam 

---

Flood 36.6°

Supply 

---

Two Circuits

Finish 

---

Matt Black



Compact exterior lighting system, to enhance outdoor public spaces, pathways and more intimate hospitality and high end residential applications.

### Product Description

The Mini G-Cat is an award winning IP66 exterior rated compact lighting system that offers versatile lighting options.

Clear polished, internally frosted Decorative Globe is joined by:

**Low Glare** A custom acrylic designed to minimise upward light spill. Suitable for Dark Sky applications.

**Technical Optics** Very Narrow – Wide Flood options supplied with low glare snoot and frosted glass with provision for one lens accessory.

### Key Features

- Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- IK10 rated.
- Adjustable beam angles with interchangeable optics with no upward light spill.
- Specialist Globe diffuser for decorative glow.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
- High-performance lighting: Up to 90 CRI LEDs



Compliance



Technical

|                    |                                                                                                                                                                     |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply             | Remote constant current LED driver required                                                                                                                         |
| Light source       | 6mm LES COB                                                                                                                                                         |
| Initial output     | 90 CRI 6.3W 9Vf at 700mA<br><br>2400K · 706lm · 119lm/W<br>2700K · 763lm · 129lm/W<br>3000K · 792lm · 134lm/W<br>3500K · 809lm · 137lm/W<br>4000K · 826lm · 140lm/W |
| Light distribution | Decorative Globe 84.4°<br>Low Glare 63.7°<br>Very Narrow 12.6°<br>Medium 25.5°<br>Flood 36.6°<br>Wide Flood 51.3°                                                   |
| Colour consistency | 3 SDCM                                                                                                                                                              |
| IP rating          | IP66                                                                                                                                                                |
| IK rating          | IK10                                                                                                                                                                |
| Weight             | 0.87kg                                                                                                                                                              |

---

Service Commitment

