STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Mushroom

STD-000411-0228

Configured Product

Length

1005mm

Finish

Matt Bronze

No. of Circuits

One (Single Colour)

Mushroom Type

Mount Disc (buried)

Circuit 1 CCT

2700K

Circuit 1 CRI

95CRI

Circuit 2 CCT

N/A

Circuit 2 CRI

N/A

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Mushroom

STD-000411-0228



Exterior landscape accent lighting system, designed for both soft and hard landscaping applications, it can be used both in ground and on tabletops.

Product Description

The Mushroom is an IP66 rated exterior accent light, designed to provide a soft, low level, wide and 360° lighting distribution via a customised impact resistant frosted diffuser system, providing a BUG rating of B0 U0 G0.
Both spike and fixed mount plates available.
Machined from recycled aluminium with an anodised and powder-coated finish for enhanced durability.

Key Features

• Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 97 CRI LEDs.
• Tuneable White and special SPD LEDs such as Reds or PC Amber are available on request.
• Ground spike and fixed mount plate options available for soft and hard landscaping applications.

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Mushroom

STD-000411-0228

Compliance

UKCA CE

ETL C US LISTED Intertek

Technical

Supply	Remote constant current LED driver required
Light source	SL Star
Initial output	**95 CRI** 8.4W 16.5Vf at 500mA 2700K • 834lm • 99lm/W 3000K • 888lm • 105lm/W 3500K • 948lm • 112lm/W 4000K • 1014lm • 120lm/W
Light distribution	Downward distribution 100.7°
Lumen maintenance	L70 B50 >66,000 hours
Colour consistency	2 SDCM
Colour maintenance	± 0.007 Δu'v'
IP rating	IP66
IK rating	IK09
Weight	0.825kg

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Mushroom

STD-000411-0228

Service Commitment

ReNew

5 Year Warranty
25 Year Duty of Care