STOANE
LIGHTING

ZTA.70.Surface.Zoom.N

STD-000527-0012

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

3000K

Finish

RAL 9010 Pure White

Attachments

None

Cable route

Through Base

Secondary Lensing Accessories


Without accessories

STOANE
LIGHTING

ZTA.70.Surface.Zoom.N

STD-000527-0012





Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description

ZTA.70.Surface.Zoom.N is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.
The spotlight can accommodate up to two lens accessories and multiple attachments, making it highly customisable for various lighting needs.
This version features a **variable zoom optic range of 17.2° to 58.5° maintaining excellent beam quality throughout**.
With a high output of up to 1419lm and CRI up to 98, it delivers exceptional performance for focused, adjustable illumination.

Key Features

• Sustainable construction: made from recycled aluminium with durable anodised and powder-coated finishes. Specialist finishes available on request.
• Variable zoom: adjustable beam from 17.2° to 58.5°, with smooth optical transition and minimal artefacting.
• High-output performance: delivered lumens up to 1419lm and CRI up to 98.
• Versatile adjustment: 363° pan and 130° tilt with lockable spot.
• Advanced dimming: local dim, DALI, 0–10V, and Wireless dimming options, down to 0.1%.
• Customisable Accessories: Can house up to two lens accessories and various attachments.
• Ceiling mounting only: designed exclusively for ceiling-mounted track installations.



STOANE
LIGHTING

ZTA.70.Surface.Zoom.N

STD-000527-0012

Compliance

STOANE LIGHTING

ZTA.70.Surface.Zoom.N

STD-000527-0012

Technical

Supply	Remote constant current LED driver required
Light source	6mm LES COB
Initial output	**SL90** 13.6W 34Vf at 400mA 2700K • 1641lm • 121lm/W 3000K • 1710lm • 126lm/W 3500K • 1727lm • 127lm/W 4000K • 1773lm • 130lm/W **SL98** 14.5W 36.4Vf at 400mA 2400K • 1115lm • 77lm/W 2700K • 1313lm • 90lm/W 3000K • 1403lm • 97lm/W 3500K • 1403lm • 97lm/W 4000K • 1481lm • 102lm/W
Light distribution	Narrow zoom extent 17.2° Wide Flood zoom extent 58.5°
Lumen maintenance	L90 B0 in excess of 94,000 hours
Colour consistency	2 SDCM
IP rating	IP20
Weight	0.84kg

STOANE
LIGHTING

ZTA.70.Surface.Zoom.N

STD-000527-0012

Service Commitment



