

Badger

STD-000532-0054

Configured Product

Light Source

SL98

Light Source Size

9mm LES

CCT

2700K

Beam

Medium 26°

Finish


Anodised Clear

Mounting Method

Adhesive by Others

Secondary Lensing Accessories

Without accessories



Exterior in-ground recessed adjustable and lockable uplighter, for enhancing architectural details, gardens and pathways.

Product Description

The Badger is a high output IP66 rated adjustable and lockable exterior up light, designed to highlight textures, add depth to trees, sculptures, facades and other outdoor features. Perfect for both commercial and residential applications, ideal for bringing landscapes to life after dark.

Machined from recycled aluminium with an anodised finish for enhanced durability and a toughened glass lens.

Key Features

- Sustainable construction: made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Adjustment providing up to $\pm 25^\circ$ of tilt and 360° of pan rotation with locking mechanism.
- Interchangeable optics to allow Very Narrow to Wide Flood with the addition of secondary lenses to create elliptical beam options.
- Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.
- High-performance lighting: Up to 98 CRI LEDs.
- First fix installation sleeve available for mounting.



Compliance



Technical

Supply	Remote constant current LED driver required
Light source	9mm LES COB
Initial output	SL90 9.1W 30.2Vf at 275 mA 2700K · 1455lm · 159lm/W 3000K · 1524lm · 167lm/W 3500K · 1540lm · 169lm/W 4000K · 1533lm · 168lm/W SL98 9W 30Vf at 300 mA 2400K · 942lm · 105lm/W 2700K · 1046lm · 116lm/W 3000K · 1117lm · 124lm/W 3500K · 1139lm · 127lm/W 4000K · 1173lm · 130lm/W
Light distribution	Narrow 18.3° Narrow 2 19.3° Medium 26° Flood 35.2° Wide Flood 46.9°
Lumen maintenance	L90 B0 in excess of 94,000 hours

Colour consistency	2 SDCM
IP rating	IP66
IK rating	IK10
Weight	2.61kg

Service Commitment

