STOANE
LIGHTING

CLP

STD-000534-0007

Configured Product

LED

COB

Light Source

SL90

CCT

3000K

Beam

TBC

Finish

Raw Aluminium

Track adaptor colour

N/A

Dimming

Driver specific

Mounting Method

Surface Mount

Cable Length


1m

STOANE LIGHTING

CLP

STD-000534-0007





Pendant shade manufactured from recycled aluminium, for enhancing dining, workspace and feature areas.

Product Description
The Cast Light Pendant (CLP) is manufactured entirely from Stoane Lighting's recycled waste aluminium stream, avoiding the need for off-site recycling and manufactured entirely in house.
Cast and machined, the product marries artisanal craftsmanship with a contemporary design, the innovative shade allows for both technical and decorative optics, additionally more traditional E27 light sources.
It can be used individually or in clusters to create dynamic lighting arrangements.

Key Features
• Sustainable construction: made from recycled aluminium.
• Height adjustable suspension with various cable colour options.
• Static and warm dim LED options available with technical optics providing Very Narrow to Wide Flood beam distributions.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 98 CRI LEDs.







STOANE LIGHTING

CLP

STD-000534-0007

Compliance

UK CA CE

Technical

Supply	Remote constant current LED driver required	
Light source	9mm LES COB	Warm Dim
Initial output	**SL90** 11.8W 33.8Vf at 350mA 2700K · 1822lm · 154lm/W 3000K · 1908lm · 161lm/W 3500K · 1929lm · 163lm/W 4000K · 1919lm · 162lm/W **SL98** 10.6W 30.4Vf at 350mA 2400K · 1085lm · 102lm/W 2700K · 1205lm · 113lm/W 3000K · 1288lm · 121lm/W 3500K · 1313lm · 124lm/W 4000K · 1352lm · 127lm/W	**90 CRI** 8.6W 34.7Vf at 250mA 3000K · 864lm · 94.9lm/W
Light distribution	Very Narrow 17° Narrow 18.6° Medium 26.1° Flood 36.2° Wide Flood 45.5° Full 129.1°	Very Narrow 17.7° Narrow 18.4° Medium 25.8° Flood 36.7° Wide Flood 47.2° Full 130°

STOANE LIGHTING

CLP

STD-000534-0007

Lumen maintenance	L90 B0 in excess of 94,000 hours (9mm LES COB)
Colour consistency	2 SDCM (9mm LES COB), 3 SDCM (Warm Dim)
IP rating	IP20
Weight	1kg

Service Commitment

ReNew

5 Year Warranty
25 Year Duty of Care