

Toad

STD-000552-0041

Configured Product

Light Source

SL98

Light Source Size

14mm LES

CCT

2700K

Beam

Medium 38.9°

Finish

Custom Painted

Attachments

None

Secondary Lensing Accessories

With accessories

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

Toad

STD-000552-0041

Compliance



Technical

| | | |
|---------------------------|--|---|
| Supply | Remote constant current LED driver required | |
| Light source | 9mm LES COB | 14mm LES COB |
| Initial output | <p>SL90 25.4W 36.3Vf at 700mA</p> <p>2700K · 3388lm · 133lm/W 3000K · 3548lm · 140lm/W 3500K · 3587lm · 141lm/W 4000K · 3569lm · 140lm/W</p> <p>SL98 30.4W 33.8Vf at 900mA</p> <p>2700K · 2740lm · 90lm/W 3000K · 2928lm · 96lm/W 3500K · 3008lm · 99lm/W 4000K · 3074lm · 101lm/W</p> | <p>SL90 30.7W 36.1Vf at 850mA</p> <p>2700K · 4232lm · 135lm/W 3000K · 4431lm · 142lm/W 3500K · 4482lm · 143lm/W 4000K · 4455lm · 143lm/W</p> <p>SL98 30.8W 34.2Vf at 900mA</p> <p>2700K · 3370lm · 109lm/W 3000K · 3600lm · 117lm/W 3500K · 3699lm · 120lm/W 4000K · 3667lm · 115lm/W</p> |
| Light distribution | <p>Very Narrow 11.6° Medium 34.7° Flood 42.8° Wide Flood 45.3°</p> | <p>Narrow 13.8° Medium 38.9° Flood 45.1° Wide Flood 52.6°</p> |
| Lumen maintenance | L90 B0 in excess of 94,000 hours | |
| Colour consistency | 2 SDCM | |
| IP rating | IP66 | |
| Weight | 2.37kg | |

Service Commitment

