

Toad

STD-000552-0060

Configured Product

Light Source

SL90

Light Source Size

9mm LES

CCT

2700K

Beam

Very Narrow 11.6°

Finish


Matt Black

Attachments

Straight/Slash Cut Snoot (specified separately)

Secondary Lensing Accessories

With accessories



High-performance exterior spotlight system, for ceiling and wall mounting to illuminate exterior architectural details and landscape illumination.

### Product Description

The Toad is a high power IP66 exterior rated, adjustable and lockable spotlight.

Constructed from precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.

Provided with interchangeable optics from Very Narrow to Wide Flood, additional lenses can be added for glare control or to create elliptical beam spreads

### Key Features

- Sustainable construction: Made from recycled aluminium with a weather resistant long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Fixed optics can be easily swapped from Very Narrow to Flood options, capable of holding up to two additional lens accessories.
- Snoot and Cowl options available.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.
- High-performance lighting: Up to 98 CRI LEDs with interchangeable optical systems.



Compliance



Technical

|                    |                                             |                            |
|--------------------|---------------------------------------------|----------------------------|
| Supply             | Remote constant current LED driver required |                            |
| Light source       | 9mm LES COB                                 | 14mm LES COB               |
| Initial output     | SL90 25.4W 36.3Vf at 700mA                  | SL90 30.7W 36.1Vf at 850mA |
|                    | 2700K · 3388lm · 133lm/W                    | 2700K · 4232lm · 135lm/W   |
|                    | 3000K · 3548lm · 140lm/W                    | 3000K · 4431lm · 142lm/W   |
|                    | 3500K · 3587lm · 141lm/W                    | 3500K · 4482lm · 143lm/W   |
|                    | 4000K · 3569lm · 140lm/W                    | 4000K · 4455lm · 143lm/W   |
|                    | SL98 30.4W 33.8Vf at 900mA                  | SL98 30.8W 34.2Vf at 900mA |
|                    | 2400K · 2467lm · 81lm/W                     | 2400K · 2982lm · 97lm/W    |
|                    | 2700K · 2740lm · 90lm/W                     | 2700K · 3370lm · 109lm/W   |
|                    | 3000K · 2928lm · 96lm/W                     | 3000K · 3600lm · 117lm/W   |
|                    | 3500K · 3008lm · 99lm/W                     | 3500K · 3699lm · 120lm/W   |
|                    | 4000K · 3074lm · 101lm/W                    | 4000K · 3667lm · 115lm/W   |
| Light distribution | Very Narrow 11.6°                           | Narrow 13.8°               |
|                    | Medium 34.7°                                | Medium 38.9°               |
|                    | Flood 42.8°                                 | Flood 45.1°                |
|                    | Wide Flood 45.3°                            | Wide Flood 52.6°           |
| Lumen maintenance  | L90 B0 in excess of 94,000 hours            |                            |
| Colour consistency | 2 SDCM                                      |                            |
| IP rating          | IP66                                        |                            |
| Weight             | 2.37kg                                      |                            |

---

Service Commitment

