STOANE
LIGHTING

Vole

STD-000553-0053

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

3000K

Beam

Flood 36.8°

Finish

Custom

Mounting Method

Adhesive/screws by others

Secondary Lensing Accessories

Without accessories

STOANE LIGHTING

Vole

STD-000553-0053





Exterior in-ground recessed fixed uplighter, for enhancing architectural details, gardens and pathways.

Product Description
The Vole is an IP66 rated fixed exterior up light, designed to highlight textures, add depth to trees, sculptures, facades and other outdoor features. Perfect for both commercial and residential applications, ideal for bringing landscapes to life after dark. Machined from recycled aluminium with an anodised finish for enhanced durability and a toughened glass lens.

Key Features
• Sustainable construction: made from recycled aluminium with a long-lasting anodised finish. Specialist finishes available on request.
• Interchangeable optics to allow Very Narrow to Wide Flood with the addition of secondary lenses to create elliptical beam options. Optional asymmetric anti-glare accessory available.
• Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 98 CRI LEDs.
• First fix installation sleeve available for mounting.





STOANE
LIGHTING

Vole

STD-000553-0053

Compliance

STOANE
LIGHTING

Vole

STD-000553-0053

Technical

Supply	Remote constant current LED driver required
Light source	6mm LES COB
Initial output	**SL90** 8W 32Vf at 250mA 2700K • 1087lm • 136lm/W 3000K • 1133lm • 141lm/W 3500K • 1144lm • 143lm/W 4000K • 1175lm • 147lm/W **SL98** 8.6W 34.4Vf at 250mA 2400K • 733lm • 85lm/W 2700K • 863lm • 100lm/W 3000K • 923lm • 107lm/W 3500K • 923lm • 107lm/W 4000K • 974lm • 113lm/W
Light distribution	Very Narrow 13.3° Narrow 14.3° Medium 24.1° Flood 36.8° Wide Flood 50.1°
Lumen maintenance	L90 B0 in excess of 94,000 hours
Colour consistency	2 SDCM
IP rating	IP66
Weight	0.5kg

STOANE
LIGHTING

Vole

STD-000553-0053

Service Commitment



