

Vole

STD-000553-0061

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

2700K

Beam

Medium 24.1°

Finish


Matt Black

Mounting Method

Adhesive/screws by others

Secondary Lensing Accessories

With accessories



Exterior in-ground recessed fixed uplighter, for enhancing architectural details, gardens and pathways.

## Product Description

The Vole is an IP66 rated fixed exterior up light, designed to highlight textures, add depth to trees, sculptures, facades and other outdoor features. Perfect for both commercial and residential applications, ideal for bringing landscapes to life after dark. Machined from recycled aluminium with an anodised finish for enhanced durability and a toughened glass lens.

## Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised finish. Specialist finishes available on request.
- Interchangeable optics to allow Very Narrow to Wide Flood with the addition of secondary lenses to create elliptical beam options. Optional asymmetric anti-glare accessory available.
- Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.
- High-performance lighting: up to 98 CRI LEDs.
- First fix installation sleeve available for mounting.



Compliance



Technical

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply             | Remote constant current LED driver required                                                                                                                                                                                                                                                                                                                                                                    |
| Light source       | 6mm LES COB                                                                                                                                                                                                                                                                                                                                                                                                    |
| Initial output     | <div>SL90 8W 32Vf at 250mA</div> <div>2700K · 1087lm · 136lm/W</div> <div>3000K · 1133lm · 141lm/W</div> <div>3500K · 1144lm · 143lm/W</div> <div>4000K · 1175lm · 147lm/W</div> <div>SL98 8.6W 34.4Vf</div> <div>at 250mA</div> <div>2400K · 733lm · 85lm/W</div> <div>2700K · 863lm · 100lm/W</div> <div>3000K · 923lm · 107lm/W</div> <div>3500K · 923lm · 107lm/W</div> <div>4000K · 974lm · 113lm/W</div> |
| Light distribution | <div>Very Narrow 13.3°</div> <div>Narrow 14.3°</div> <div>Medium 24.1°</div> <div>Flood 36.8°</div> <div>Wide Flood 50.1°</div>                                                                                                                                                                                                                                                                                |
| Lumen maintenance  | L90 B0 in excess of 94,000 hours                                                                                                                                                                                                                                                                                                                                                                               |
| Colour consistency | 2 SDCM                                                                                                                                                                                                                                                                                                                                                                                                         |
| IP rating          | IP66                                                                                                                                                                                                                                                                                                                                                                                                           |
| Weight             | 0.5kg                                                                                                                                                                                                                                                                                                                                                                                                          |

---

Service Commitment

