STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

# Vole

STD-000553-0066

## Configured Product

Light Source

SL98

Light Source Size

6mm LES

CCT

2400K

Beam

Medium 24.1°

Finish

Matt Black

Mounting Method

Adhesive/screws by others

Secondary Lensing Accessories

With accessories

**STOANE** LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

# Vole

STD-000553-0066




Exterior in-ground recessed fixed uplighter, for enhancing architectural details, gardens and pathways.

**Product Description**

The Vole is an IP66 rated fixed exterior up light, designed to highlight textures, add depth to trees, sculptures, facades and other outdoor features. Perfect for both commercial and residential applications, ideal for bringing landscapes to life after dark. Machined from recycled aluminium with an anodised finish for enhanced durability and a toughened glass lens.

**Key Features**

• Sustainable construction: made from recycled aluminium with a long-lasting anodised finish. Specialist finishes available on request.
• Interchangeable optics to allow Very Narrow to Wide Flood with the addition of secondary lenses to create elliptical beam options. Optional asymmetric anti-glare accessory available.
• Advanced dimming options: DALI, 0-10V, and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 98 CRI LEDs.
• First fix installation sleeve available for mounting.

**STOANE** LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

# Vole

STD-000553-0066

## Compliance

# Vole

STD-000553-0066

## Technical

| | |
|---|---|
| **Supply** | Remote constant current LED driver required |
| **Light source** | 6mm LES COB |
| **Initial output** | **SL90** 8W 32Vf at 250mA<br>2700K • 1087lm • 136lm/W<br>3000K • 1133lm • 141lm/W<br>3500K • 1144lm • 143lm/W<br>4000K • 1175lm • 147lm/W<br>**SL98** 8.6W 34.4Vf at 250mA<br>2400K • 733lm • 85lm/W<br>2700K • 863lm • 100lm/W<br>3000K • 923lm • 107lm/W<br>3500K • 923lm • 107lm/W<br>4000K • 974lm • 113lm/W |
| **Light distribution** | Very Narrow 13.3°<br>Narrow 14.3°<br>Medium 24.1°<br>Flood 36.8°<br>Wide Flood 50.1° |
| **Lumen maintenance** | L90 B0 in excess of 94,000 hours |
| **Colour consistency** | 2 SDCM |
| **IP rating** | IP66 |
| **Weight** | 0.5kg |

**STOANE** LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

# Vole

STD-000553-0066

---

## Service Commitment

---