

## ZTA.35.Surface

STD-000558-0094

### Configured Product

Light source

6mm LES

CCT

3000K

CRI

SL90

Beam

Medium 23°

Finish

TBC

Cable route

TBC

Secondary Lensing Accessories

With accessories

## Compliance



## Technical

<b>Supply</b>	Remote constant current LED driver required	
<b>Light source</b>	4mm LES COB	6mm LES COB
<b>Initial output</b>	<p><b>SL90</b> 8.8W 35.1Vf at 250mA</p> <p>2700K · 972lm · 111lm/W            3000K · 1013lm · 115lm/W            3500K · 1023lm · 116lm/W            4000K · 1051lm · 120lm/W</p> <p><b>SL98</b> 4.3W 17.2Vf at 250mA</p> <p>2700K · 418lm · 97lm/W            3000K · 446lm · 104lm/W            3500K · 446lm · 104lm/W            4000K · 471lm · 110lm/W</p>	<p><b>SL90</b> 8W 32Vf at 250mA</p> <p>2700K · 1087lm · 136lm/W            3000K · 1133lm · 141lm/W            3500K · 1144lm · 143lm/W            4000K · 1175lm · 147lm/W</p> <p><b>SL98</b> 8.6W 34.4Vf at 250mA</p> <p>2700K · 863lm · 100lm/W            3000K · 923lm · 107lm/W            3500K · 923lm · 107lm/W            4000K · 974lm · 113lm/W</p>
<b>Light distribution</b>	<p>Narrow 13.6°            Medium 22°            Flood 35.4°            Wide Flood 52.8°            Zoom 17.2° - 46.8°</p>	<p>Narrow 17.8°            Medium 23°            Flood 34.6°            Wide Flood 54.5°            Zoom 21.6° - 44.9°</p>
<b>Lumen maintenance</b>	L90 B0 in excess of 94,000 hours	

Colour consistency	2 SDCM
Colour maintenance	$\pm 0.007 \Delta u'v'$
IP rating	IP20
Weight	0.31kg

---

## Service Commitment

