

# ZTA.35.Surface

STD-000558-0124

## Configured Product

Light source

4mm LES

CCT

3000K

CRI

SL90

Beam

Medium 22°

Finish

RAL 9010 Pure White

Cable route

Through Base

Secondary Lensing Accessories

With accessories

Compliance



Technical

|                    |                                             |                           |
|--------------------|---------------------------------------------|---------------------------|
| Supply             | Remote constant current LED driver required |                           |
| Light source       | 4mm LES COB                                 | 6mm LES COB               |
| Initial output     | SL90 8.8W 35.1Vf at 250mA                   | SL90 8W 32Vf at 250mA     |
|                    | 2700K · 972lm · 111lm/W                     | 2700K · 1087lm · 136lm/W  |
|                    | 3000K · 1013lm · 115lm/W                    | 3000K · 1133lm · 141lm/W  |
|                    | 3500K · 1023lm · 116lm/W                    | 3500K · 1144lm · 143lm/W  |
|                    | 4000K · 1051lm · 120lm/W                    | 4000K · 1175lm · 147lm/W  |
|                    | SL98 4.3W 17.2Vf at 250mA                   | SL98 8.6W 34.4Vf at 250mA |
|                    | 2700K · 418lm · 97lm/W                      | 2700K · 863lm · 100lm/W   |
|                    | 3000K · 446lm · 104lm/W                     | 3000K · 923lm · 107lm/W   |
|                    | 3500K · 446lm · 104lm/W                     | 3500K · 923lm · 107lm/W   |
|                    | 4000K · 471lm · 110lm/W                     | 4000K · 974lm · 113lm/W   |
| Light distribution | Narrow 13.6°                                | Narrow 17.8°              |
|                    | Medium 22°                                  | Medium 23°                |
|                    | Flood 35.4°                                 | Flood 34.6°               |
|                    | Wide Flood 52.8°                            | Wide Flood 54.5°          |
|                    | Zoom 17.2° - 46.8°                          | Zoom 21.6° - 44.9°        |
| Lumen maintenance  | L90 B0 in excess of 94,000 hours            |                           |

|                    |                         |
|--------------------|-------------------------|
| Colour consistency | 2 SDCM                  |
| Colour maintenance | $\pm 0.007 \Delta u'v'$ |
| IP rating          | IP20                    |
| Weight             | 0.31kg                  |

---

## Service Commitment

