STOANE
LIGHTING

ZTA.35.Surface

STD-000558-0143

Configured Product

Light Source

SL90

Light Source Size

4mm LES

CCT

2700K

Beam

Medium 22°

Finish

Custom

Cable route

Through Base

Secondary Lensing Accessories

Without accessories

STOANE
LIGHTING

ZTA.35.Surface

STD-000558-0143

Compliance

UK CA CE

c ETL LISTED us
Intertek

STOANE LIGHTING

ZTA.35.Surface

STD-000558-0143

Technical

Supply	Remote constant current LED driver required	
Light source	4mm LES COB	6mm LES COB
Initial output	**SL90** 8.8W 35.1Vf at 250mA 2700K • 972lm • 111lm/W 3000K • 1013lm • 115lm/W 3500K • 1023lm • 116lm/W 4000K • 1051lm • 120lm/W **SL98** 4.3W 17.2Vf at 250mA 2400K • 355lm • 83lm/W 2700K • 418lm • 97lm/W 3000K • 446lm • 104lm/W 3500K • 446lm • 104lm/W 4000K • 471lm • 110lm/W	**SL90** 8W 32Vf at 250mA 2700K • 1087lm • 136lm/W 3000K • 1133lm • 141lm/W 3500K • 1144lm • 143lm/W 4000K • 1175lm • 147lm/W **SL98** 8.6W 34.4Vf at 250mA 2400K • 733lm • 85lm/W 2700K • 863lm • 100lm/W 3000K • 923lm • 107lm/W 3500K • 923lm • 107lm/W 4000K • 974lm • 113lm/W
Light distribution	Narrow 13.6° Medium 22° Flood 35.4° Wide Flood 52.8° Zoom 17.2° - 46.8°	Narrow 17.8° Medium 23° Flood 34.6° Wide Flood 54.5° Zoom 21.6° - 44.9°
Lumen maintenance	L90 B0 in excess of 94,000 hours	
Colour consistency	2 SDCM	
IP rating	IP20	
Weight	0.31kg	

STOANE
LIGHTING

ZTA.35.Surface

STD-000558-0143

Service Commitment

ReNew

5 Year Warranty
25 Year Duty of Care