STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.35.Surface

STD-000558-0152

Configured Product

Light Source

SL90

Light Source Size

4mm LES

CCT

3000K

Beam

Medium 22°

Finish

Matt Black

Cable route

Through Base

Secondary Lensing Accessories

Without accessories

Compliance

Technical

Supply	Remote constant current LED driver required	
Light source	4mm LES COB	6mm LES COB
Initial output	**SL90** 8.8W 35.1Vf at 250mA 2700K • 972lm • 111lm/W 3000K • 1013lm • 115lm/W 3500K • 1023lm • 116lm/W 4000K • 1051lm • 120lm/W **SL98** 4.3W 17.2Vf at 250mA 2400K • 355lm • 83lm/W 2700K • 418lm • 97lm/W 3000K • 446lm • 104lm/W 3500K • 446lm • 104lm/W 4000K • 471lm • 110lm/W	**SL90** 8W 32Vf at 250mA 2700K • 1087lm • 136lm/W 3000K • 1133lm • 141lm/W 3500K • 1144lm • 143lm/W 4000K • 1175lm • 147lm/W **SL98** 8.6W 34.4Vf at 250mA 2400K • 733lm • 85lm/W 2700K • 863lm • 100lm/W 3000K • 923lm • 107lm/W 3500K • 923lm • 107lm/W 4000K • 974lm • 113lm/W
Light distribution	Narrow 13.6° Medium 22° Flood 35.4° Wide Flood 52.8° Zoom 17.2° - 46.8°	Narrow 17.8° Medium 23° Flood 34.6° Wide Flood 54.5° Zoom 21.6° - 44.9°
Lumen maintenance	L90 B0 in excess of 94,000 hours	
Colour consistency	2 SDCM	
IP rating	IP20	
Weight	0.31kg	

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.35.Surface

STD-000558-0152

Service Commitment