

## ZTA.35.Surface

STD-000558-0164

### Configured Product

Light Source

SL98

Light Source Size

6mm LES

CCT

3000K

Beam

Custom

Finish


TBC

Cable route

TBC

Secondary Lensing Accessories

With accessories



Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Easily interchangeable between fixed and Zoom optics.

## Product Description

ZTA.35.Surface is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. The spotlight can accommodate up to two lens accessories with fixed optics or a single lens accessory with Zoom and multiple attachments, making it highly customisable for various lighting needs.

## Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Fixed optics can be easily swapped to Zoom.
- Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: can house up to one lens accessory and various attachments.



**STOANE LIGHTING**

EQUIPMENT DESIGN + MANUFACTURE

ZTA.35.Surface

STD-000558-0164

Compliance



# Technical

<b>Supply</b>	Remote constant current LED driver required	
<b>Light source</b>	4mm LES COB	6mm LES COB
<b>Initial output</b>	<p><b>SL90</b> 8.8W 35.1Vf at 250mA</p> <p>2700K · 972lm · 111lm/W                  3000K · 1013lm · 115lm/W                  3500K · 1023lm · 116lm/W                  4000K · 1051lm · 120lm/W</p> <p><b>SL98</b> 4.3W 17.2Vf at 250mA</p> <p>2700K · 418lm · 97lm/W                  3000K · 446lm · 104lm/W                  3500K · 446lm · 104lm/W                  4000K · 471lm · 110lm/W</p>	<p><b>SL90</b> 8W 32Vf at 250mA</p> <p>2700K · 1087lm · 136lm/W                  3000K · 1133lm · 141lm/W                  3500K · 1144lm · 143lm/W                  4000K · 1175lm · 147lm/W</p> <p><b>SL98</b> 8.6W 34.4Vf at 250mA</p> <p>2700K · 863lm · 100lm/W                  3000K · 923lm · 107lm/W                  3500K · 923lm · 107lm/W                  4000K · 974lm · 113lm/W</p>
<b>Light distribution</b>	<p>Narrow 13.6°                  Medium 22°                  Flood 35.4°                  Wide Flood 52.8°                  Zoom 17.2° - 46.8°</p>	<p>Narrow 17.8°                  Medium 23°                  Flood 34.6°                  Wide Flood 54.5°                  Zoom 21.6° - 44.9°</p>
<b>Lumen maintenance</b>	L90 B0 in excess of 94,000 hours	
<b>Colour consistency</b>	2 SDCM	
<b>IP rating</b>	IP20	
<b>Weight</b>	0.31kg	

## Service Commitment

