STOANE
LIGHTING

ZTA.35.Surface

STD-000558-0168

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

2700K

Beam

Medium 23°

Finish

RAL 9010 Pure White

Cable route

Through Base

Secondary Lensing Accessories

With accessories

STOANE
LIGHTING

ZTA.35.Surface

STD-000558-0168

Compliance

STOANE LIGHTING

ZTA.35.Surface

STD-000558-0168

Technical

Supply	Remote constant current LED driver required	
Light source	4mm LES COB	6mm LES COB
Initial output	**SL90** 8.8W 35.1Vf at 250mA 2700K · 972lm · 111lm/W 3000K · 1013lm · 115lm/W 3500K · 1023lm · 116lm/W 4000K · 1051lm · 120lm/W	**SL90** 8W 32Vf at 250mA 2700K · 1087lm · 136lm/W 3000K · 1133lm · 141lm/W 3500K · 1144lm · 143lm/W 4000K · 1175lm · 147lm/W
	SL98 4.3W 17.2Vf at 250mA 2400K · 355lm · 83lm/W 2700K · 418lm · 97lm/W 3000K · 446lm · 104lm/W 3500K · 446lm · 104lm/W 4000K · 471lm · 110lm/W	**SL98** 8.6W 34.4Vf at 250mA 2400K · 733lm · 85lm/W 2700K · 863lm · 100lm/W 3000K · 923lm · 107lm/W 3500K · 923lm · 107lm/W 4000K · 974lm · 113lm/W
Light distribution	Narrow 13.6° Medium 22° Flood 35.4° Wide Flood 52.8° Zoom 17.2° - 46.8°	Narrow 17.8° Medium 23° Flood 34.6° Wide Flood 54.5° Zoom 21.6° - 44.9°
Lumen maintenance	L90 B0 in excess of 94,000 hours	
Colour consistency	2 SDCM	
IP rating	IP20	
Weight	0.31kg	

STOANE
LIGHTING

ZTA.35.Surface

STD-000558-0168

Service Commitment



