STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

# ZTA.35.Surface

STD-000558-0175

## Configured Product

Light Source

SL98

Light Source Size

6mm LES

CCT

3000K

Beam

Zoom 21.6° - 44.9°

Finish

Matt Black

Cable route

Flying Lead

Secondary Lensing Accessories

Without accessories

## Compliance

# Technical

| | | |
|---|---|---|
| **Supply** | Remote constant current LED driver required | |
| **Light source** | 4mm LES COB | 6mm LES COB |
| **Initial output** | **SL90** 8.8W 35.1Vf at 250mA<br><br>2700K • 972lm • 111lm/W<br>3000K • 1013lm • 115lm/W<br>3500K • 1023lm • 116lm/W<br>4000K • 1051lm • 120lm/W<br><br>**SL98** 4.3W 17.2Vf at 250mA<br><br>2400K • 355lm • 83lm/W<br>2700K • 418lm • 97lm/W<br>3000K • 446lm • 104lm/W<br>3500K • 446lm • 104lm/W<br>4000K • 471lm • 110lm/W | **SL90** 8W 32Vf at 250mA<br><br>2700K • 1087lm • 136lm/W<br>3000K • 1133lm • 141lm/W<br>3500K • 1144lm • 143lm/W<br>4000K • 1175lm • 147lm/W<br><br>**SL98** 8.6W 34.4Vf at 250mA<br><br>2400K • 733lm • 85lm/W<br>2700K • 863lm • 100lm/W<br>3000K • 923lm • 107lm/W<br>3500K • 923lm • 107lm/W<br>4000K • 974lm • 113lm/W |
| **Light distribution** | Narrow 13.6°<br>Medium 22°<br>Flood 35.4°<br>Wide Flood 52.8°<br>Zoom 17.2° - 46.8° | Narrow 17.8°<br>Medium 23°<br>Flood 34.6°<br>Wide Flood 54.5°<br>Zoom 21.6° - 44.9° |
| **Lumen maintenance** | L90 B0 in excess of 94,000 hours | |
| **Colour consistency** | 2 SDCM | |
| **IP rating** | IP20 | |
| **Weight** | 0.31kg | |

**STOANE** LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

# ZTA.35.Surface

STD-000558-0175

## Service Commitment