STOANE
LIGHTING

# ZTA.35.Surface

STD-000558-0178

## Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

3000K

Beam

TBC

Finish

Standard Painted

Cable route

Through Base

Secondary Lensing Accessories

Without accessories

STOANE
LIGHTING

# ZTA.35.Surface

STD-000558-0178

## Compliance

STOANE LIGHTING

# ZTA.35.Surface

STD-000558-0178

## Technical

| | | |
|---|---|---|
| **Supply** | Remote constant current LED driver required | |
| **Light source** | 4mm LES COB | 6mm LES COB |
| **Initial output** | **SL90** 8.8W 35.1Vf at 250mA<br>2700K · 972lm · 111lm/W<br>3000K · 1013lm · 115lm/W<br>3500K · 1023lm · 116lm/W<br>4000K · 1051lm · 120lm/W<br>**SL98** 4.3W 17.2Vf at 250mA<br>2400K · 355lm · 83lm/W<br>2700K · 418lm · 97lm/W<br>3000K · 446lm · 104lm/W<br>3500K · 446lm · 104lm/W<br>4000K · 471lm · 110lm/W | **SL90** 8W 32Vf at 250mA<br>2700K · 1087lm · 136lm/W<br>3000K · 1133lm · 141lm/W<br>3500K · 1144lm · 143lm/W<br>4000K · 1175lm · 147lm/W<br>**SL98** 8.6W 34.4Vf at 250mA<br>2400K · 733lm · 85lm/W<br>2700K · 863lm · 100lm/W<br>3000K · 923lm · 107lm/W<br>3500K · 923lm · 107lm/W<br>4000K · 974lm · 113lm/W |
| **Light distribution** | Narrow 13.6°<br>Medium 22°<br>Flood 35.4°<br>Wide Flood 52.8°<br>Zoom 17.2° - 46.8° | Narrow 17.8°<br>Medium 23°<br>Flood 34.6°<br>Wide Flood 54.5°<br>Zoom 21.6° - 44.9° |
| **Lumen maintenance** | L90 B0 in excess of 94,000 hours | |
| **Colour consistency** | 2 SDCM | |
| **IP rating** | IP20 | |
| **Weight** | 0.31kg | |

STOANE
LIGHTING

# ZTA.35.Surface

STD-000558-0178

## Service Commitment




