STOANE
LIGHTING

ZTA.50.Mains Track.Wall Wash

STD-000560-0009

Configured Product

Light Source

SL90

Light Source Size

9mm LES

CCT

2700K

Finish

Matt Black

Track adaptor colour

White

Dimming

DALI

Attachments

None

Secondary Lensing Accessories

Without accessories

STOANE LIGHTING

ZTA.50.Mains Track.Wall Wash

STD-000560-0009





Modular high-performance, mains track-mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments.
Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description
ZTA.50.Mains Track.Wall Wash is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between fixed optic, Zoom and Framing projector options.

Key Features
• Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Wall Wash optics can be easily swapped to Fixed, Zoom and additional framer attachments.
• Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
• Broad compatibility: 3-circuit adapter supports multiple track systems (Stucchi, Eutrac, Global Pulse).
• Advanced dimming options: On-board, DALI, 0-10V, and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
• Customisable accessories: can house up to two lens accessory and various attachments.
• Ceiling mounting only: designed exclusively for ceiling installations.

Compliance

STOANE LIGHTING

ZTA.50.Mains Track.Wall Wash

STD-000560-0009

Technical

Supply	230V/240V via 3 circuit track
Light source	9mm LES COB
Initial output	**SL90** 11.8W 33.8Vf at 350mA 2700K • 1822lm • 154lm/W 3000K • 1908lm • 161lm/W 3500K • 1929lm • 163lm/W 4000K • 1919lm • 162lm/W **SL98** 10.6W 30.4Vf at 350mA 2400K • 1085lm • 102lm/W 2700K • 1205lm • 113lm/W 3000K • 1288lm • 121lm/W 3500K • 1313lm • 124lm/W 4000K • 1352lm • 127lm/W
Light distribution	Wall Wash 75.6° x 30.5°
Lumen maintenance	L90 B0 in excess of 94,000 hours
Colour consistency	2 SDCM
IP rating	IP20
Weight	0.5kg

STOANE
LIGHTING

ZTA.50.Mains Track.Wall Wash

STD-000560-0009

Service Commitment



