

ZTA.50.Surface.Wall Wash

STD-000562-0012

Configured Product

Light Source

SL90

Light Source Size

9mm LES

CCT

Custom

Supply

Constant Current

Finish

TBC

Dimming

Driver specific

Attachments

None

Attachments


None

Cable route

TBC

Secondary Lensing Accessories

With accessories



Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments.

Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description

ZTA.70.Surface.Wall Wash is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.

Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- High-performance lighting: up to 98 CRI LEDs.
- Customisable accessories: can house up to two lens accessories and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.

Compliance



Technical

Supply Remote constant current LED driver required

Light source 9mm LES COB

Initial output **SL90** 11.8W 33.8Vf at 350mA

2700K · 1822lm · 154lm/W

3000K · 1908lm · 161lm/W

3500K · 1929lm · 163lm/W

4000K · 1919lm · 162lm/W

SL98 10.6W 30.4Vf at

350mA

2700K · 1205lm · 113lm/W

3000K · 1288lm · 121lm/W

3500K · 1313lm · 124lm/W

4000K · 1352lm · 127lm/W

Light distribution Wall Wash 75.6° x 30.5°

Lumen maintenance L90 B0 in excess of 94,000 hours

Colour consistency 2 SDCM

IP rating IP20

Weight 0.39kg

Service Commitment

