STOANE
LIGHTING

# ZTA.50.Surface.Wall Wash

STD-000562-0015

## Configured Product

Light Source

SL90

Light Source Size

9mm LES

CCT

2700K

Supply

Constant Current

Finish

Custom Painted

Dimming

Driver specific

Attachments

None

Attachments

Barn Doors (specified separately)

Cable route

Flying Lead

Secondary Lensing Accessories

With accessories

STOANE LIGHTING

# ZTA.50.Surface.Wall Wash

STD-000562-0015






Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments.
Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

**Product Description**
ZTA.70.Surface.Wall Wash is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.

**Key Features**
• Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
• High-performance lighting: up to 98 CRI LEDs.
• Customisable accessories: can house up to two lens accessories and various attachments.
• Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.

## Compliance

UKCA CE

ETL C US LISTED Intertek

STOANE LIGHTING

# ZTA.50.Surface.Wall Wash

STD-000562-0015

## Technical

| | |
|---|---|
| **Supply** | Remote constant current LED driver required |
| **Light source** | 9mm LES COB |
| **Initial output** | **SL90** 11.8W 33.8Vf at 350mA<br><br>2700K • 1822lm • 154lm/W<br>3000K • 1908lm • 161lm/W<br>3500K • 1929lm • 163lm/W<br>4000K • 1919lm • 162lm/W<br><br>**SL98** 10.6W 30.4Vf at 350mA<br><br>2400K • 1085lm • 102lm/W<br>2700K • 1205lm • 113lm/W<br>3000K • 1288lm • 121lm/W<br>3500K • 1313lm • 124lm/W<br>4000K • 1352lm • 127lm/W |
| **Light distribution** | Wall Wash 75.6° x 30.5° |
| **Lumen maintenance** | L90 B0 in excess of 94,000 hours |
| **Colour consistency** | 2 SDCM |
| **IP rating** | IP20 |
| **Weight** | 0.39kg |

STOANE
LIGHTING

# ZTA.50.Surface.Wall Wash

STD-000562-0015

## Service Commitment




