

ZTA.50.Bay

STD-000564-0063

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

3000K

Beam

Very Narrow 13.9°

Finish

Matt Black

Dimming


Driver specific

Cable Length

500mm

Secondary Lensing Accessories

Without accessories



Modular high-performance, ceiling mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

### Product Description

ZTA.50.Bay is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics.

### Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: can house up to two lens accessories and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



Compliance



Technical

|                    |                                             |                            |
|--------------------|---------------------------------------------|----------------------------|
| Supply             | Remote constant current LED driver required |                            |
| Light source       | 6mm LES COB                                 | 9mm LES COB                |
| Initial output     | SL90 8W 32Vf at 250mA                       | SL90 11.8W 33.8Vf at 350mA |
|                    | 2700K · 1087lm · 136lm/W                    | 2700K · 1822lm · 154lm/W   |
|                    | 3000K · 1133lm · 141lm/W                    | 3000K · 1908lm · 161lm/W   |
|                    | 3500K · 1144lm · 143lm/W                    | 3500K · 1929lm · 163lm/W   |
|                    | 4000K · 1175lm · 147lm/W                    | 4000K · 1919lm · 162lm/W   |
|                    | SL98 8.6W 34.4Vf at 250mA                   | SL98 10.6W 30.4Vf at 350mA |
|                    | 2400K · 733lm · 85lm/W                      | 2400K · 1085lm · 102lm/W   |
|                    | 2700K · 863lm · 100lm/W                     | 2700K · 1205lm · 113lm/W   |
|                    | 3000K · 923lm · 107lm/W                     | 3000K · 1288lm · 121lm/W   |
|                    | 3500K · 923lm · 107lm/W                     | 3500K · 1313lm · 124lm/W   |
| Light distribution | Very Narrow 13.9°                           | Narrow 17.4°               |
|                    | Narrow 14.7°                                | Narrow 2 18.8°             |
|                    | Medium 24.1°                                | Medium 25.3°               |
|                    | Flood 36.7°                                 | Flood 34.1°                |
|                    | Wide Flood 51.7°                            | Wide Flood 46.6°           |
| Lumen maintenance  | L90 B0 in excess of 94,000 hours            |                            |
| Colour consistency | 2 SDCM                                      |                            |
| IP rating          | IP20                                        |                            |
| Weight             | 0.31kg                                      |                            |

---

Service Commitment

