STOANE
LIGHTING

ZTA.50.Mains Track.Zoom

STD-000572-0054

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

3000K

Beam

Zoom 13.7° to 48.1°

Finish

Matt Black

Track adaptor colour

White

Dimming

DALI

Attachments

Barn Doors (specified separately)

Secondary Lensing Accessories

With accessories

STOANE LIGHTING

ZTA.50.Mains Track.Zoom

STD-000572-0054





Modular high-performance, mains track-mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments. Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description

ZTA.50.Mains Track.Zoom is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between fixed optic, Wall Wash and Framing projector options.

Key Features

• Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
• Zoom optics can be easily swapped to Fixed, Wall Wash and additional framer attachments.
• Versatile Adjustment: 363° pan rotation and 130° tilt with a lockable spot.
• Broad compatibility: 3-circuit adapter supports multiple track systems (Stucchi, Eutrac, Global Pulse).
• Advanced dimming options: On-board, DALI, 0-10V, and Wireless dimming, down to 0.1%.
• High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
• Customisable accessories: can house up to one lens accessory and various attachments.
• Ceiling mounting only: designed exclusively for ceiling installations.

Compliance

UKCA CE

ETL LISTED c US Intertek

STOANE LIGHTING

ZTA.50.Mains Track.Zoom

STD-000572-0054

Technical

Supply	230V/240V via 3 circuit track
Light source	6mm LES COB
Initial output	**SL90** 8W 32Vf at 250mA 2700K • 1087lm • 136lm/W 3000K • 1133lm • 141lm/W 3500K • 1144lm • 143lm/W 4000K • 1175lm • 147lm/W **SL98** 8.6W 34.4Vf at 250mA 2400K • 733lm • 85lm/W 2700K • 863lm • 100lm/W 3000K • 923lm • 107lm/W 3500K • 923lm • 107lm/W 4000K • 974lm • 113lm/W
Light distribution	**Zoom** 13.7° – 48.1°
Lumen maintenance	L90 B0 in excess of 94,000 hours
Colour consistency	2 SDCM
IP rating	IP20
Weight	0.56kg

STOANE
LIGHTING

ZTA.50.Mains Track.Zoom

STD-000572-0054

Service Commitment



