

## ZTA.50.Surface

STD-000577-0315

### Configured Product

Light Source

SL98

Light Source Size

4mm LES

CCT

2700K

Beam

Medium 24.2

Supply

Constant Current

Finish

RAL 9010 Pure White

Dimming

Driver specific

Attachments

Barn Doors (specified separately)

Cable route

Through Base

Cable Length

500mm

Secondary Lensing Accessories

# STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

With accessories



**STOANE LIGHTING**

EQUIPMENT DESIGN + MANUFACTURE

ZTA.50.Surface

STD-000577-0315

Compliance



# Technical

<b>Supply</b>	Remote constant current LED driver required		
<b>Light source</b>	4mm LES COB	6mm LES COB	9mm LES COB
<b>Initial output</b>	<p><b>SL90</b> 8.8W 35.1Vf at 250mA</p> <p>2700K · 972lm · 111lm/W                  3000K · 1013lm · 115lm/W                  3500K · 1023lm · 116lm/W                  4000K · 1051lm · 120lm/W</p> <p><b>SL98</b> 4.3W 17.2Vf at 250mA</p> <p>2700K · 418lm · 97lm/W                  3000K · 446lm · 104lm/W                  3500K · 446lm · 104lm/W                  4000K · 471lm · 110lm/W</p>	<p><b>SL90</b> 8W 32Vf at 250mA</p> <p>2700K · 1087lm · 136lm/W                  3000K · 1133lm · 141lm/W                  3500K · 1144lm · 143lm/W                  4000K · 1175lm · 147lm/W</p> <p><b>SL98</b> 8.6W 34.4Vf at 250mA</p> <p>2700K · 863lm · 100lm/W                  3000K · 923lm · 107lm/W                  3500K · 923lm · 107lm/W                  4000K · 974lm · 113lm/W</p>	<p><b>SL90</b> 11.8W 33.8Vf at 350mA</p> <p>2700K · 1822lm · 154lm/W                  3000K · 1908lm · 161lm/W                  3500K · 1929lm · 163lm/W                  4000K · 1919lm · 162lm/W</p> <p><b>SL98</b> 10.6W 30.4Vf at 350mA</p> <p>2700K · 1205lm · 113lm/W                  3000K · 1288lm · 121lm/W                  3500K · 1313lm · 124lm/W                  4000K · 1352lm · 127lm/W</p>
<b>Light distribution</b>	<p>Very Narrow 8.8°                  Narrow 11°                  Medium 24.2°                  Flood 39.7°                  Wide Flood 49.4°</p>	<p>Very Narrow 13.9°                  Narrow 14.7°                  Medium 24.1°                  Flood 36.7°                  Wide Flood 51.7°</p>	<p>Narrow 17.4°                  Narrow 2 18.8°                  Medium 25.3°                  Flood 34.1°                  Wide Flood 46.6°</p>
<b>Lumen maintenance</b>	L90 B0 in excess of 94,000 hours		
<b>Colour consistency</b>	2 SDCM		
<b>IP rating</b>	IP20		
<b>Weight</b>	0.39kg		

## Service Commitment

