

ZTA.50.Surface.Zoom

STD-000578-0026

Configured Product

Light Source

Custom

Light Source Size

Custom

CCT

Custom

Beam

Custom

Finish

RAL 9010 Pure White

Dimming

Driver specific

Attachments


None

Cable route

Through Base

Secondary Lensing Accessories

With accessories



Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments
 Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

Product Description

ZTA.50.Surface Zoom is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between fixed optic, Wall Wash, Zoom and Framing projector options.

Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Zoomable beam to allow easy and quick beam adjustment without the need for additional optics.
- Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: can house up to one lens accessory and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

ZTA.50.Surface.Zoom

STD-000578-0026

Compliance



Technical

Supply Remote constant current LED driver required

Light source 6mm LES COB

Initial output **SL90** 8W 32Vf at 250mA
2700K · 1087lm · 136lm/W
3000K · 1133lm · 141lm/W
3500K · 1144lm · 143lm/W
4000K · 1175lm · 147lm/W

SL98 8.6W 34.4Vf at
250mA

2700K · 863lm · 100lm/W
3000K · 923lm · 107lm/W
3500K · 923lm · 107lm/W
4000K · 974lm · 113lm/W

Light distribution Zoom 13.7° - 48.1°

Lumen maintenance L90 B0 in excess of 94,000 hours

Colour consistency 2 SDCM

IP rating IP20

Weight 0.43kg

Service Commitment

