

ZTA.50.Surface.Zoom

STD-000578-0035

Configured Product

Light Source

SL90

Light Source Size

6mm LES

CCT

2700K

Beam

Zoom 13.7° to 48.1°

Finish

RAL 9010 Pure White

Dimming

Driver specific

Attachments


Straight/Slash Cut Snoot (specified separately)

Cable route

Through Base

Secondary Lensing Accessories

With accessories



Modular high-performance, surface mounted spotlight system, for interior architectural applications such as Museums, Galleries, Retail and Workplace environments

Engineered for exceptional durability, maintainability, re-manufacturability, and recyclability, this spotlight sets a new standard for sustainable design.

## Product Description

ZTA.50.Surface Zoom is constructed from extruded and precision-machined recycled aluminium, the spotlight features an anodised and powder-coated finish for enhanced durability and aesthetics. Easily interchangeable between fixed optic, Wall Wash, Zoom and Framing projector options.

## Key Features

- Sustainable construction: made from recycled aluminium with a long-lasting anodised and powder-coated finish. Specialist finishes available on request.
- Zoomable beam to allow easy and quick beam adjustment without the need for additional optics.
- Versatile adjustment: 363° pan rotation and 130° tilt with a lockable spot.
- High-performance lighting: up to 98 CRI LEDs with interchangeable optical systems.
- Customisable accessories: can house up to one lens accessory and various attachments.
- Advanced dimming options: DALI, 0-10V, DMX and Wireless dimming, down to 0.1%.



Compliance



Technical

|                    |                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply             | Remote constant current LED driver required                                                                                                                                                                                                                                                                                                                                                         |
| Light source       | 6mm LES COB                                                                                                                                                                                                                                                                                                                                                                                         |
| Initial output     | <div>SL90 8W 32Vf at 250mA</div> <div>2700K · 1087lm · 136lm/W</div> <div>3000K · 1133lm · 141lm/W</div> <div>3500K · 1144lm · 143lm/W</div> <div>4000K · 1175lm · 147lm/W</div> <div>SL98 8.6W 34.4Vf at 250mA</div> <div>2400K · 733lm · 85lm/W</div> <div>2700K · 863lm · 100lm/W</div> <div>3000K · 923lm · 107lm/W</div> <div>3500K · 923lm · 107lm/W</div> <div>4000K · 974lm · 113lm/W</div> |
| Light distribution | Zoom 13.7° - 48.1°                                                                                                                                                                                                                                                                                                                                                                                  |
| Lumen maintenance  | L90 B0 in excess of 94,000 hours                                                                                                                                                                                                                                                                                                                                                                    |
| Colour consistency | 2 SDCM                                                                                                                                                                                                                                                                                                                                                                                              |
| IP rating          | IP20                                                                                                                                                                                                                                                                                                                                                                                                |
| Weight             | 0.43kg                                                                                                                                                                                                                                                                                                                                                                                              |

---

Service Commitment

